



Model:	Pre-rinse spray unit EcoStar
Order no.:	1507
Description:	<p>Pre-rinse spray unit single-hole mixer tap and stem tap</p> <ul style="list-style-type: none"> <li>• Non-return upper parts prevent a circulation of warm and cold water as well as the back siphonage of sewage. These fittings therefore comply with regulations for drinking water installations according to DIN 1988.</li> <li>• with metal cap handle</li> <li>• chrome plated suspension spring</li> <li>• Ergonomically designed, easy-to-use hand-held rinser (plastic housing with brass cartridge), resistant to pressure shock due to integrated delayed closing action</li> <li>• Stable Niro braided hose with transparent plastic sheathing and EPDM- inner hose assembly equates to KTW- reference</li> <li>• wall socket without visible thread, can be shortened from 165mm to 35mm</li> <li>• connection with flexible hoses with G3/8" cap nut</li> <li>• flow rate between 9 l/min and 15 l/min at 2 to 4 bar</li> <li>• all solders are free from cadmium and lead</li> <li>• all gaskets comply with KTW regulations and the DVGW worksheet W 270 (covering the use of plastics in drinking water, cold, warm and hot water applications)</li> <li>• bore hole Ø 30 mm</li> </ul>
Danger warning:	<p>To prevent any damage by water, the upper parts of the mixer should be closed after business hours.</p> <p>The Pre-rinse spray units may not be used to clean sliding dishwashers. There is a risk of damaging the hose through pulling it to strongly.</p>
Care instruction:	<p>Clean the surfaces with standard eco-friendly care products. Do not use any kind of scrubbing agents, steel wool, or any cleaning agents containing a high concentration of acid or chlorides!</p> <p>Do not, in accordance with the worksheet Vdf 018, use high pressure cleaning equipment!</p>